Stainless Steel Aircraft Cable

Type 304

7x7	
7x19	

Size (in)	Construction	Weight/1000 Ft (Ibs)	Breaking Strength (lbs)
1/16	7x7	7.5	480
3/32	7x7	16	920
1/8	7x7	28	1700
3/16	7x7	62	3700
1/8	7x19	29	1700
5/32	7x19	45	2400
3/16	7x19	65	3700
7/32	7x19	86	5000
1/4	7x19	110	6400
5/16	7x19	173	9000
3/8	7x19	243	12,000

Standard Reel Lengths in Stock: 250', 500', 1,000' & 5,000'

Stainless Steel Aircraft Cable

Type 316

7x19

Stanness Steer A	Type 510		
Size (in)	Construction	Weight/1000 Ft (Ibs)	Breaking Strength (Ibs)
1/8	7x19	29	1670
3/16	7x19	65	3565
1/4	7x19	110	5875
5/16	7x19	173	8825
3/8	7x19	243	11,760

Standard Reel Lengths in Stock: 250', 500', 1,000' & 5,000'

According to Federal Specification RR-W-410D

6x25 Stainless Steel Wire Rope IWRC

Type 304

6X25 IWRC	

6X36 IWRC

Size (in)	Weight/Ft (Ibs)	Breaking Strength (Ibs)
7/16	.36	16,300
1/2	.46	22,800
9/16	.59	28,500
5/8	.72	35,000
3/4	1.04	49,600
7/8	1.42	58,000
1	1.85	75,200

6x36 Stainless Steel Wire Rope IWRC

Type 304

8	0x30 Stanness Steel W	туре	
>	Size (in)	Weight/Ft (Ibs)	Breaking Strength (lbs)
	3/8	.24	11,700
	1/2	.46	15,800
	9/16	.54	18,300
	5/8	.72	25,600