

Wire Rope Slings



Eye & Eye



Eye & Thimble

Sliding Choker



Eye & Eye



Eye & Thimble












Eye & Hook



Thimble & Hook



Thimble & Thimble

					Minimum Sling Length	Standard Eye Size (in) WxL			
	Rope Diameter (in)	Vertical	Choker	Vertical Basket			Thimble Eye Size (in) WxL	Eye Hook Cap. (tons)	Sliding Choker Hook (in)
 <p>6x19</p>	1/4	0.65	0.48	1.3	1' 6"	2x4	7/8x1-5/8	1	3/8
	5/16	1.0	0.74	2.0	1' 9"	2-1/2x5	1-1/16x1-7/8	1	3/8
	3/8	1.4	1.1	2.9	2' 0"	3x6	1-1/8x2-1/8	1 1/2	3/8
	7/16	1.9	1.4	3.9	2' 3"	3-1/2x7	1-1/4x 2-1/4	2	1/2
	1/2	2.5	1.9	5.1	2' 6"	4x8	1-1/2x 2-3/4	3	1/2
	9/16	3.2	2.4	6.4	2' 9"	4-1/2x9	1-1/2x2-3/4	5	5/8
	5/8	3.9	2.9	7.8	3' 0"	5x10	1-3/4x3-1/4	5	5/8
	3/4	5.6	4.1	11	3' 6"	6x12	2x3-1/4	7	3/4
	7/8	7.6	5.6	15	4' 0"	7x14	2-1/4x4-1/4	11	7/8
	1	9.8	7.2	20	4' 6"	8x16	2-1/2x 4-1/2	11	1
 <p>6x37</p>	1-1/8	12	9.1	24	5' 0"	9x18	2 7/8x5-1/8	15	1-1/8
	1-1/4	15	11	30	5' 6"	10x20	3-1/2x6-1/2	15	1-1/4
	1-3/8	18	13	36	6' 0"	11x22	3-1/2x6-1/4	22	1-3/8
	1-1/2	21	16	42	7' 0"	12x24	3-1/2x6-1/4	22	1-1/2
	1-3/4	28	21	57	8' 0"	14x28	4-1/2x9	30	
	2	37	28	73	9' 0"	16x32	6x12	37	
	2-1/4	44	35	89	10' 0"	18x36	7x14	45	
2-1/2	54	42	103	11' 0"	20x40				

Note: Larger diameter slings available

1. 1 Ton=2,000lbs

2. Minimum sling length when using standard eyes

WARNING

Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°.