

## NEW & EXCLUSIVE

SUPERTECHLON® Round Slings offer an enhanced combination of strength and flexibility with an abrasion resistant outer jacket.

### Features and Benefits

All the benefits of a polyester round sling:

- Abrasion-resistant Techlon™ outer cover delivers up to twice the durability of a standard cover
- Stripe coded to assist in identifying sling capacity (each stripe equals 3000 lbs of vertical capacity) — rated higher than Industry standard
- Visible print coded with vertical lifting capacity printed on the outer cover
- Color coded for ease of identification
- All in one fly tags and identification tag for ease of use
- Individually serialized for traceability




### Capacity Chart & Specifications


All capacities listed below meet or exceed ASME B30.9 standards requiring a 5:1 design factor when new and un-used.

Code	Color	Rated Capacity (lbs.)			Minimum Length (ft.)	Relaxed Body Diameter (in.)	Sleeve Width (in.)	Approximate Weight (lbs/ft)
		Vertical <sup>1</sup>	Choker <sup>2</sup>	Basket <sup>3</sup>				
ST-ENR-3000	PURPLE	3,000	2,400	6,000	3'	0.63"	1.50"	0.3 <i>Basket</i>
ST-ENR-6000	GREEN	6,000	4,800	12,000	3'	0.88"	1.75"	0.4
ST-ENR-9000	YELLOW	9,000	7,200	18,000	3'	1.13"	2.13"	0.6
ST-ENR-12000	TAN	12,000	9,600	24,000	3'	1.25"	2.13"	0.7
ST-ENR-15000	RED	15,000	12,000	30,000	3'	1.56"	2.69"	0.9
ST-ENR-18000	WHITE	18,000	14,400	36,000	3'	1.63"	2.88"	1.0
ST-ENR-24000	BLUE	24,000	19,200	48,000	4'	2.00"	3.50"	1.7
ST-ENR-30000	ORANGE	30,000	24,000	60,000	4'	2.56"	4.72"	2.0

Slings are made to order up to 40ft in length.

**HOW TO ORDER INSTRUCTIONS = CODE - LENGTH - D**





**⚠ WARNING**

SLING FAILURE CAN CAUSE  
**DEATH OR INJURY**

SLING FAILURE RESULTS FROM MISUSE, DAMAGE, AND EXCESSIVE WEAR

---

ADHERE TO INDUSTRY STANDARDS & REGULATIONS

**⚠ WARNING**

**PROTECT SLINGS FROM CUTTING:**

FAILURE TO PROTECT SLING FROM CUTTING MAY RESULT IN DAMAGE, INJURY OR DEATH. CONTACT US TO DISCUSS SLING PROTECTION OPTIONS.

