

CR30 Proof Coil Chain

Size (inches)	Weight/Ft (lbs.)	Working Load Limit (lbs.)
1/8"	0.17	375
3/16"	0.40	750
1/4"	0.68	1250
5/16"	1.02	1900
3/8"	1.47	2650
1/2"	2.40	4500
5/8"	3.58	6900
3/4"	5.48	10,600
7/8"	7.31	12,800

CR43 High Test Chain

Size (inches)	Weight/Ft (lbs.)	Working Load Limit (lbs.)
1/4"	0.71	2600
5/16"	0.98	3900
3/8"	1.44	5400
1/2"	2.78	9200
5/8"	3.58	11,500
3/4"	5.48	16,200
1/4"	0.71	2600
5/16"	0.98	3900
3/8"	1.44	5400

CR70 Transport

Size (inches)	Weight/Ft (lbs.)	Working Load Limit (lbs.)
1/4"	0.63	3150
5/16"	0.93	4700
3/8"	1.41	6600
1/2"	2.40	11,300

CR80 Alloy

Size (inches)	Weight/Ft (lbs.)	Working Load Limit (lbs.)
9/32"	0.72	3500
5/16"	0.92	4500
3/8"	1.50	7100
1/2"	2.61	12,000
5/8"	3.61	18,100
3/4"	5.40	28,300
7/8"	7.13	34,200
1"	9.48	47,700

CR100 Alloy

Size (inches)	Weight/Ft (lbs.)	Working Load Limit (lbs.)
9/32"	0.74	4300
5/16"	1.10	5700
3/8"	1.48	8800
1/2"	2.50	15,000
5/8"	3.79	22,600
3/4"	5.98	35,300