

Swage Fittings

Aluminum Swage Fittings



Size (in)	Pieces per Pack	Weight/100 pcs (lbs) Sleeves	Weight/100 pcs (lbs) Stops
1/16	100	.10	.060
3/32	100	.32	.23
1/8	100	.66	.21
5/32	100	.80	.37
3/16	100	1.52	.35
1/4	100	2.52	2.10
5/16	100	4.35	
3/8	100	5.82	

Copper Swage Fittings



Size (in)	Pieces per Pack	Weight/100 pcs (lbs) Sleeves	Weight/100 pcs (lbs) Stops
1/16	100	.29	.19
3/32	100	.60	.78
1/8	100	1.62	.90
5/32	100	2.28	1.20
3/16	100	5.20	1.05
1/4	100	7.85	6.10
5/16	100	11.86	5.20
3/8	100	15.80	4.58

When properly applied- Aluminum Swage Sleeves are capable of supporting 95% of the rated breaking strength of the cable to which they are applied. Copper Swage Sleeves are capable of holding the rated breaking strength of the aircraft cable.

Stops are capable of holding 1/3 to 1/2 the rated breaking strength.

Stainless Steel Swage Sleeves

Type 304



Size (in)	Pieces per Pack	Weight/100 pcs (lbs)
3/64	100	.16
1/16	100	.16
3/32	100	.16
1/8	100	.37
5/32	100	1.4
3/16	100	2.0
7/32	100	3.1
1/4	100	4.0